

# Specifications

## OPTICAL OXYGEN 230-MINISENSORS

---

### 1 SENSOR SPECIFICATIONS

**Only valid in water/gas (typ. air components) for 2-point calibrated sensors at 20°C, 1013mbar absolute pressure, using default measuring parameters/modes!**

Specifications are valid for retractable minisensors (item no.: **OXR230**) and bare fiber minisensors (item no.: **OXB230**), including the following options: optical isolation (-OI), high speed (-HS), ultra-high speed (-UHS).

#### 1.1 Gas Phase: partial pressure pO<sub>2</sub> (hPa), volume percent pV (% O<sub>2</sub> gas)

For a calibrated sensor, the partial oxygen pressure pO<sub>2</sub> in units of hPa (equivalent to mbar) is the fundamental oxygen unit measured by the oxygen meter (in gas and water phase).

##### Specifications

Measuring Range	% O <sub>2</sub> gas	hPa
Optimum	0-50% O <sub>2</sub>	0-500 hPa
Maximum (not specified)	0-100% O <sub>2</sub>	0-1000 hPa
Accuracy *		
at 1% O <sub>2</sub> /10 hPa	±0.02% O <sub>2</sub>	±0.2 hPa
at 20% O <sub>2</sub> /200 hPa	±0.2% O <sub>2</sub>	±2 hPa
Resolution		
at 1% O <sub>2</sub> /10 hPa	0.01% O <sub>2</sub>	0.1 hPa
at 20% O <sub>2</sub> /200 hPa	0.05% O <sub>2</sub>	0.5 hPa
Detection Limit	0.02% O <sub>2</sub>	0.2 hPa

\* The absolute accuracy of full range sensors depends on the calibration mode. For 1-point calibrated sensors these values increase due to a decreasing accuracy. More details on request.

## 1.2 Dissolved Oxygen: % air saturation, $\mu\text{mol/L}$ , $\text{mg/L}$ = $\text{ppm}$ , $\text{mL/L}$

Oxygen dissolved in water can be expressed in % air saturation and in concentration units like  $\mu\text{mol/L}$ ,  $\text{mg/L}$  (ppm), and  $\text{mL/L}$ . For details on calculation of dissolved oxygen units from partial pressure readings (interpolation formula based on temperature, atmospheric pressure and salinity), please see the respective sensor/oxygen meter manuals.

Specifications		
<b>Measuring Range</b> Optimum Maximum (not specified)	<b>% air saturation (a.s.)</b> 0-250% a.s. 0-500% a.s.	<b>mg/L (ppm)</b> 0-22 mg/L 0-44 mg/L
<b>Accuracy *</b> at 5% a.s./0.44 mg/L at 95% a.s./8.8 mg/L	$\pm 0.1\%$ a.s. $\pm 1\%$ a.s.	$\pm 0.01$ mg/L $\pm 0.1$ mg/L
<b>Resolution</b> at 5% a.s./0.44 mg/L at 95% a.s./8.8 mg/L	0.05% a.s. 0.25% a.s.	0.005 mg/L 0.025 mg/L
<b>Detection Limit</b>	0.1% a.s.	0.01 mg/L

\* The absolute accuracy of the full range sensors depends on the calibration mode. For 1-point calibrated sensors these values increase due to a decreasing accuracy. More details on request.

## 1.3 General Characteristics


<b>Response Time (t90) ‡</b> Gas (standard / with -OI) Water (standard / with -OI) High Speed (-HS) Ultra-High Speed (-UHS)	<1 sec / <4 sec <2 sec / <10 sec <0.8 sec <0.3 sec		
<b>Temperature Range</b>	specified: 0°C (32°F) to 50°C (122°F) not specified: -20°C (-4°F) to 70°C (158°F)		
<b>Minimum Lifetime</b> data points	standard / -OI 1,000,000	-HS <1,000,000	-UHS <<1,000,000
<b>Calibration Modes</b>	1-point and 2-point calibration; obligatory to calibrate in gas ( <i>water</i> ) calibration standards for measurements in gas ( <i>water</i> ) samples		
<b>Sensor Dimensions: OXR230</b> Length without cable (ca.) Shaft diameter (ca.)	230 mm 8 mm		

<b>Needle Dimensions: OXR230</b> Length Diameter	40 mm 0.5 mm
<b>Fiber and Sensor Tip: OXR230</b> Fiber & tip diameter Sensor tip position (rel. to needle)	230 $\mu$ m ca. -6/0/+6/+12 mm
<b>Sensor Dimensions: OXB230</b> Fiber & tip diameter Tip geometry Stripping lengths	230 $\mu$ m see image and text below A = 20mm, B = 100mm (other stripping lengths optional on request)
<b>Cable length</b>	ca. 2 m or ca. 4 m (custom versions up to ca. 20 m)
<b>Application Areas</b>	Laboratory, industry, research. <b>NOT</b> for medical or any safety-critical application. <b>NOT</b> for application in humans. <b>NOT</b> for application in food intended for human consumption.

‡ Typical response times for 90% signal change. For liquids: measured for the transition from air into a stirred solution of 1% Na<sub>2</sub>SO<sub>3</sub>

### Tip Geometry: OXB230

True to scale drawings with outer jacket (brown), plastic coating (grey), optical fiber (pink) and oxygen sensitive REDFLASH indicator (green).



## 2 APPLICABILITY AND CROSS-SENSITIVITY

	Applicability	Cross-Sensitivity	NO Cross-Sensitivity
Water/Aqueous solutions	X		
Gas Phase (typ. air components)	X		
Ethanol <sup>1,2</sup>	short-term only		
Methanol <sup>1,2</sup>	short-term only		
Isopropanol <sup>1,2</sup>	short-term only		
Other organic solvents <sup>3</sup>		X	
Chlorine gas (Cl <sub>2</sub> ), NO <sub>2</sub> gas, bleach		X	
pH 1-14			X
CO <sub>2</sub>			X
CH <sub>4</sub>			X
H <sub>2</sub> S			X
Any ionic species			X

<sup>1</sup> Not applicable for sensors with optical isolation (-OI).

<sup>2</sup> Only diluted and after conditioning- contact [info@pyroscience.com](mailto:info@pyroscience.com) for more information.

<sup>3</sup> Includes liquid solvents and solvent vapors

### 3 CLEANING, STERILIZATION, STORAGE

<b>Cleaning</b>	3% H <sub>2</sub> O <sub>2</sub> , soap solution, short-term ethanol
<b>Sterilization</b>	short-term 70% ethanol*, short-term 70% isopropanol*, ethylene oxide (EtO, EO) sterilization (details on request)
<b>Storage</b>	>3 years in darkness at room temperature

\* Not applicable for sensors with optical isolation (-OI).

#### Contact

**PyroScience GmbH**  
Kackertstraße 11  
52072 Aachen  
Deutschland

Tel.: +49 (0)241 5183 2210  
Fax: +49 (0)241 5183 2299  
info@pyroscience.com  
www.pyroscience.com