

# Specifications

## OPTICAL TEMPERATURE MINISENSORS

---

### 1 SENSOR SPECIFICATIONS

Specifications are valid for retractable needle-type minisensors (item no.: **TPR430**), fixed needle-type minisensors (item no.: **TPF1100**), bare fiber minisensors (item no.: **TPB430**) and insertable mini probes (item no.: **TPIMP500**) including the following options: underwater connector (-**SUB**).

#### 1.1 Specifications in gas & water/aqueous samples

Specifications	
Measuring Range	0 to 50°C (273-323 K; 32-122 °F)
Accuracy	± 0.5°C (1-point calibrated)
Resolution	0.02°C
Drift	<0.1°C / day

\* For 1-point calibrated sensor.

#### 1.2 General Characteristics

Response time ‡ (t90) in water	<0.1 sec
Minimum Lifetime	10,000,000 data points
Calibration Modes	1-point calibration
Application Areas	Laboratory, industry, research. <b>NOT</b> for medical or any safety-critical application. <b>NOT</b> for application in humans. <b>NOT</b> for application in food intended for human consumption.

‡ Typical response times for 90% signal change.

## 2 APPLICABILITY AND CROSS-SENSITIVITY

	Applicability	Cross-Sensitivity
Water/Aqueous solutions	X	
Gas Phase (typ. air components)	X	
Organic solvents*		X
Bleach		X

\* Includes liquid solvents and solvent vapors

## 3 CLEANING, STERILIZATION, STORAGE

<b>Cleaning</b>	3% H <sub>2</sub> O <sub>2</sub> , soap solution
<b>Sterilization</b>	ethylene oxide (EtO, EO) sterilization (details on request)
<b>Storage</b>	>3 years in darkness at room temperature

### Contact

**PyroScience GmbH**  
Kackertstraße 11  
52072 Aachen  
Deutschland

Tel.: +49 (0)241 5183 2210  
Fax: +49 (0)241 5183 2299  
info@pyroscience.com  
www.pyroscience.com