

# Price List

## FireSting Sensors

---

### 1 PRICES OXYGEN SENSORS (ST-CONNECTOR)

Only valid within the EU, for overseas prices please contact us!

#### 1.1 Fiber Oxygen Sensors for FireSting Devices

For more available sensors and custom versions, please contact us!

Item	Description (Needle / Tip Diameter)	Price in EUR
<b>OXROB3</b>	Robust Oxygen Probe (3mm / 30mm)	240
<b>OXROB3-CL4</b>	Robust Oxygen Probe (3mm / 30mm), cable length 4m	270
<b>OXROB10</b>	Robust Oxygen Probe (3mm / 100mm)	240
<b>OXROB10-CL4</b>	Robust Oxygen Probe (3mm / 100mm), cable length 4m	270
<b>TROXROB3</b>	Robust TRACE Oxygen Probe (3mm / 30mm)	240
<b>TROXROB10</b>	Robust TRACE Oxygen Probe (3mm / 100mm)	240
<b>OXR50</b>	Retractable Oxygen Microsensor (0.5mm / ca. 50-70µm)	230
<b>OXR50-CL4</b>	Retractable Oxygen Microsensor (0.5mm / ca. 50-70µm), Cable Length 4m	260
<b>OXR50-OI</b>	Retractable Oxygen Microsensor (0.5mm / ca.40-60µm), Optical Isolation	290
<b>OXR50-OI-CL4</b>	Retractable Oxygen Microsensor (0.5mm / ca.40-60µm), Optical Isolation, Cable Length 4m	320
<b>OXR50-HS</b>	Retractable Oxygen Microsensor (0.5mm / ca. 50-70µm), High Speed	260
<b>OXR50-UHS</b>	Retractable Oxygen Microsensor (0.5mm / ca. 50-70µm), Ultra-High Speed	290

<b>OXR50-UHS-CL4</b>	Retractable Oxygen Microsensor (0.5mm / ca. 50-70µm), Ultra-High Speed, Cable Length 4m	320
<b>OXR430</b>	Retractable Oxygen Minisensor (1.1mm / 430 µm)	290
<b>OXR430-CL4</b>	Retractable Oxygen Minisensor (1.1mm / 430 µm), Cable Length 4 m	320
<b>OXR430-OI</b>	Retractable Oxygen Minisensor (1.1mm / 430 µm), Optical Isolation	350
<b>OXR430-OI-CL4</b>	Retractable Oxygen Minisensor (1.1mm / 430 µm), Optical Isolation, Cable Length 4m	380
<b>OXR430-HS</b>	Retractable Oxygen Minisensor (1.1mm / 430 µm), High Speed	320
<b>OXR430-HS-CL4</b>	Retractable Oxygen Minisensor (1.1mm / 430 µm), High Speed, Cable Length 4m	350
<b>OXR430-UHS</b>	Retractable Oxygen Minisensor (1.1mm / 430 µm), Ultra-High Speed	350
<b>TROXR430</b>	Retractable TRACE Oxygen Minisensor (1.1mm / 430 µm)	290
<b>OXF50</b>	Fixed Oxygen Microsensor (0.5mm / ca. 50-70µm)	230
<b>OXF50-OI</b>	Fixed Oxygen Microsensor (0.5mm / ca. 50-70µm), Optical Isolation	290
<b>OXF50-HS</b>	Fixed Oxygen Microsensor (0.5mm / ca. 50-70µm), High Speed	260
<b>OXF50-UHS</b>	Fixed Oxygen Microsensor (0.5mm / ca. 50-70µm), Ultra-High Speed	290
<b>OXF1100</b>	Fixed Oxygen Minisensor (1.2mm / 430µm)	290
<b>OXF1100-CL4</b>	Fixed Oxygen Minisensor (1.2mm / 430µm), Cable Length 4m	320
<b>OXF1100-OI</b>	Fixed Oxygen Minisensor (1.2mm / 430µm), Optical Isolation	350
<b>OXF1100-OI-CL4</b>	Fixed Oxygen Minisensor (1.2mm / 430µm), Optical Isolation, Cable Length 4m	380
<b>OXF1100-HS</b>	Fixed Oxygen Minisensor (1.2mm / 430µm), High Speed	320
<b>OXF1100-UHS</b>	Fixed Oxygen Minisensor (1.2mm / 430µm), Ultra-High Speed	350
<b>TROXF1100</b>	Fixed TRACE Oxygen Minisensor (1.2mm / 430µm)	290
<b>TROXF1100-CL4</b>	Fixed TRACE Oxygen Minisensor (1.2mm / 430µm), Cable Length 4m	320
<b>OXF500PT</b>	Protected Tip Oxygen Minisensor (0.5mm / 230µm)	290

<b>OXF500PT-OI</b>	Protected Tip Oxygen Minisensor (0.5mm / 230µm), Optical Isolation	350
<b>OXF500PT-OI-CL4</b>	Protected Tip Oxygen Minisensor (0.5mm / 230µm), Optical Isolation, Cable Length 4m	380
<b>OXF900PT</b>	Protected Tip Oxygen Minisensor (0.9mm / 230µm)	290
<b>OXF900PT-OI</b>	Protected Tip Oxygen Minisensor (0.9mm / 230µm), Optical Isolation	350
<b>OXB430</b>	Bare Fiber Oxygen Microsensor (430 µm)	260
<b>OXB430-OI</b>	Bare Fiber Oxygen Minisensor (430 µm), Optical Isolation	320
<b>OXB430-HS</b>	Bare Fiber Oxygen Microsensor (430 µm), High Speed	290
<b>OXB430-UHS</b>	Bare Fiber Oxygen Microsensor (430 µm), Ultra-High Speed	320
<b>OXB430-UHS-CL4</b>	Bare Fiber Oxygen Microsensor (430 µm), Ultra-High Speed, Cable Length 4m	350
<b>TROXB430</b>	Bare Fiber TRACE Oxygen Minisensor (430 µm)	260
<b>OXB50</b>	Bare Fiber Oxygen Microsensor (ca. 50-70µm)	220
<b>OXB50-CL4</b>	Bare Fiber Oxygen Microsensor (ca. 50-70µm), Cable Length 4m	250
<b>OXB50-OI</b>	Bare Fiber Oxygen Microsensor (ca.40-60µm), Optical Isolation	280
<b>OXB50-OI-CL4</b>	Bare Fiber Oxygen Microsensor (ca.40-60µm), Optical Isolation, Cable Length 4m	310
<b>OXB50-HS</b>	Bare Fiber Oxygen Microsensor (ca. 50-70µm), High Speed	250
<b>OXB50-UHS</b>	Bare Fiber Oxygen Microsensor (ca. 50-70µm), Ultra-High Speed	280
<b>OX SOLV</b>	Solvent-Resistant Oxygen Probe (1.5mm / 150mm) Unprotected Protruding Tip	490
<b>OX SOLV-PTS</b>	Solvent-Resistant Oxygen Probe (1.5mm / 40mm) Protected Tip	490

## 1.2 Contactless Oxygen Sensors for FireSting Devices

For more available sensors and custom versions, please contact us!

Item	Description	Price in EUR
<b>OXFTC</b>	Flow-Through Cell with optical oxygen sensor, small (PU= 2 pieces)	200
<b>OXFTC2</b>	Flow-Through Cell with optical oxygen sensor, large (PU= 2 pieces)	200
<b>TROXFTC</b>	Flow-Through Cell with TRACE optical oxygen sensor, small (PU= 2 pieces)	200
<b>TROXFTC2</b>	Flow-Through Cell with TRACE optical oxygen sensor, large (PU= 2 pieces)	200
<b>TOFTC2</b>	Flow-Through Cell with optical oxygen and temperature sensor, large (PU= 2 pieces)	300
<b>OXFTCR</b>	Flow-Through Cell with removable optical oxygen sensor	270
<b>OXNANO</b>	Oxygen Nanoprobes (PU = 5 x 10mg).	580
<b>OXSP5</b>	Oxygen Sensor Spots (PU = 8 pieces)	240
<b>TROXSP5</b>	TRACE Oxygen Sensor Spot (PU = 8 pieces)	240
<b>OXVIAL4</b>	Vial (ca. 4 mL) with integrated optical oxygen sensor (PU = 4 pieces)	240
<b>OXVIAL20</b>	Vial (ca. 20 mL) with integrated optical oxygen sensor (PU = 4 pieces)	240
<b>TOVIAL20</b>	Vial (ca. 20 mL) with integrated optical oxygen and temperature sensor (PU = 4 pieces)	360

## 2 PRICES OPTICAL PH SENSORS

Only valid within the EU, for overseas prices please contact us!

### 2.1 Fiber-optic pH Sensors (only for FireSting-PRO)

For more available sensors and custom versions, please contact us!

Item	Description	Price in EUR
PHROBSC-PK5	Robust pH Screw Cap Probe (4mm / 100mm), pH range 4.0 - 6.0, with 4 sensor screw caps	320
PHROBSC-PK6	Robust pH Screw Cap Probe (4mm / 100mm), pH range 5.0-7.0, with 4 sensor screw caps	320
PHROBSC-PK7	Robust pH Screw Cap Probe (4mm / 100mm), pH range 6.0 - 8.0, with 4 sensor screw caps	320
PHROBSC-PK8	Robust pH Screw Cap Probe (4mm / 100mm), pH range 7.0-9.0, with 4 sensor screw caps	320
PHSC-PK5	Sensor screw caps with pH range 4.0 - 6.0 for robust screw cap probe, (PU = 4 pieces)	120
PHSC-PK6	Sensor screw caps with pH range 5.0 -7.0 for robust screw cap probe, (PU = 4 pieces)	120
PHSC-PK7	Sensor screw caps with pH range 6.0 - 8.0 for robust screw cap probe, (PU = 4 pieces)	120
PHSC-PK8	Sensor screw caps with pH range 7.0 -9.0 for robust screw cap probe, (PU = 4 pieces)	120

## 2.2 Contactless pH Sensors (only for FireSting-PRO)

For more available sensors and custom versions, please contact us!

Item	Description	Price in EUR
PHFTCR-PK7	Flow-through cell with removable pH probe, pH range 6.0-8.0 (PU = 1 piece)	270
PHFTCR-PK8	Flow-through cell with removable pH probe, pH range 7.0-9.0 (PU = 1 piece)	270
PHSP5-PK5	pH Sensor Spots, pH range 4.0 - 6.0, (PU = 8 pieces)	240
PHSP5-PK6	pH Sensor Spots, pH range 5.0 - 7.0, (PU = 8 pieces)	240
PHSP5-PK7	pH Sensor Spots, pH range 6.0 - 8.0, (PU = 8 pieces)	240
PHSP5-PK8	pH Sensor Spots, pH range 7.0 - 9.0, (PU = 8 pieces)	240
PHVIAL4-PK7	Vial (ca. 4 mL) with integrated optical pH sensor, pH range 6.0 - 8.0 (PU = 4 pieces)	280
PHVIAL4-PK8	Vial (ca. 4 mL) with integrated optical pH sensor, pH range 7.0 - 9.0 (PU = 4 pieces)	280
PHVIAL20-PK7	Vial (ca. 20 mL) with integrated optical pH sensor, pH range 6.0 - 8.0 (PU = 4 pieces)	280
PHVIAL20-PK8	Vial (ca. 20 mL) with integrated optical pH sensor, pH range 7.0 - 9.0 (PU = 4 pieces)	280
PHTVIAL20-PK7	Vial (ca. 20 mL) with integrated optical pH & temperature sensor, pH range 6.0 - 8.0 (PU = 4 pieces)	400
PHTVIAL20-PK8	Vial (ca. 20 mL) with integrated optical pH & temperature sensor, pH range 7.0 - 9.0 (PU = 4 pieces)	400
PHTOVIAL20-PK7	Vial (ca. 20 mL) with integrated optical pH, oxygen & temperature sensor, pH range 6.0 - 8.0 (PU = 2 pieces)	290
PHTOVIAL20-PK8	Vial (ca. 20 mL) with integrated optical pH, oxygen & temperature sensor, pH range 7.0 - 9.0 (PU = 2 pieces)	290

## 3 PRICES OPTICAL TEMPERATURE SENSORS

Only valid within the EU, for overseas prices please contact us!

### 3.1 Fiber Temperature Sensors for FSO<sub>2</sub> / FSPRO Devices

For more available sensors and custom versions, please contact us!

Item	Description	Price in EUR
TPR430	Retractable Needle-Type Temperature Minisensor (1.1mm / 430µm)	290
TPF1100	Fixed Needle-Type Temperature Minisensor (1.1mm / 430µm)	290
TPB430	Bare Fiber Temperature Minisensor (430µm)	260

### 3.2 Contactless Temperature Sensors FSO<sub>2</sub> / FSPRO Devices

For more available sensors and custom versions, please contact us!

Item	Description	Price in EUR
TPSP5	Optical Temperature Sensor Spots (PU=8 pieces)	240
TPFTC2	Flow-Through Cell with optical temperature sensor, large (PU= 2 pieces)	200

## 4 PRICES FOR SENSOR ACCESSORIES

Only valid within the EU, for overseas prices please contact us!

### 4.1 Accessories for Contactless Sensors (O<sub>2</sub>, pH and T)

Item	Description	Price in EUR
<b>SPADBAS</b>	Basic Spot Adapter for fixing SPFIB or SPFIB-LNS at windows (PU=4 pieces) Read-out of <b>OXSP5, TPSP5, PHSP5, OXNANO</b>	50
<b>SPFIB-BARE</b>	Bare Optical Fiber, ST-plug + one polished end, cable length 1m With all contactless sensors	50
<b>SPFIB-BARE-CL2</b>	Bare Optical Fiber, ST-plug + one polished end, cable length 2m With all contactless sensors	60
<b>SPFIB-LNS</b>	Optical fiber with integrated lens for FireSting devices, cable length 1m Read-out of <b>OXNANO, OXSP5, TPSP5, PHSP5</b> through >2mm walls	260
<b>SPFIB-LNS-CL2</b>	Optical fiber with integrated lens for FireSting devices, cable length 2m Read-out of <b>OXNANO, OXSP5, TPSP5, PHSP5</b> through >2mm walls	290
<b>SPGLUE</b>	Silicone Glue for fixing sensor spots + <b>SPADBAS</b> at transparent container walls. For gluing all sensor spots	30
<b>SPGLUE-KIT</b>	Gluing kit with 1 spoon spatula ( <b>SPTLA</b> ), 1 disposable syringe with screw cap, 5 flat needles. For gluing all sensor spots	50
<b>SPTLA</b>	Spoon spatula, 300 mm length, for handling sensor spots	30
<b>ADVIAL4</b>	Adapter ring for 4mL vials with 1 sensor	30
<b>ADVIAL20</b>	Adapter ring for 20mL vials with 1 sensor	30
<b>ADVIAL20T</b>	Adapter ring for 20mL vials with up to 3 sensors	30
<b>ADVIAL4KIT</b>	Adapter kit including adapter rings ADVIAL4 & SPFIB-BARE-CL2 for connection to FSO <sub>2</sub> / FSPRO (PU = 4 pieces)	290
<b>ADVIAL20-KIT</b>	Adapter kit including adapter rings ADVIAL20 & SPFIB-BARE-CL2 for connection to FSO <sub>2</sub> / FSPRO (PU = 4 pieces)	290
<b>ADVIAL20T-KIT</b>	Adapter kit including adapter rings ADVIAL20T & SPFIB-BARE-CL2 for connection to FSO <sub>2</sub> /FSPRO (PU = 4 pieces)	290
<b>SEPVIAL4</b>	Septa with lids (with and without hole), for replacement in 4mL vials (PU=4 pieces)	20



<b>SEPVIAL20</b>	Septa with lids (with and without hole), for replacement in 20mL vials (PU=4 pieces)	20
------------------	--	----

## 4.2 Accessories for Calibration (O<sub>2</sub>, pH) and Application

<b>Item</b>	<b>Description</b>	<b>Price in EUR</b>
<b>OXCAL</b>	Calibrations capsules for 50ml 0% O <sub>2</sub> solution, PU=10 For 0% calibration of all O <sub>2</sub> sensors (except <b>OXNANO</b> )	44
<b>PHCAL2</b>	Buffer capsules for 100ml buffer (pH 2.0), PU = 10 Calibration of all pH sensors	44
<b>PHCAL10</b>	Buffer capsules for 100ml buffer (pH 10.0), PU = 10 Calibration of all pH sensors	44
<b>ADPATCH</b>	Adhesive sticker patches (PU=10 pcs.), Ø15mm, transparent, for piercing with protected tip oxygen minisensors	10

## 5 PT100 TEMPERATURE PROBES (WITH LEMO-CONNECTOR)

Only valid within the EU, for overseas prices please contact us!

Item	Description	Price in EUR
TDIP15	Temperature Sensor for FireSting devices, shielded dipping probe Ø1.5mm	140
TSUB21	Temperature Sensor for FireSting devices, Teflon-coated & submersible, cable length 2m, for long-term submersion in water	140
TSUB21-CL1	Temperature Sensor for FireSting devices, Teflon-coated & submersible, cable length 1m, for solvent-resistant probes & sensors with 1m cable length	140
TSUB21-CL5	Temperature Sensor for FireSting devices, Teflon-coated & submersible, cable length 5m, for sensors with 4m cable length	160

### Contact

**PyroScience GmbH**  
Hubertusstraße 35  
52064 Aachen  
Deutschland

Tel.: +49 (0)241 5183 2210  
Fax: +49 (0)241 5183 2299  
info@pyroscience.com  
www.pyroscience.com